



The AC-PLUS-T, AC-SLIM, AC-MAX, AC-45, AC-PRO-II and AC-MANAGE are equipped with the INTELLI-SENSE Smart Charging System. This system will initiate an test of your devices charging level requirements. Devices which are plugged into power strips that draw the most power will take priority. Once devices are fully charged, the system will remain in a trickle charging state, maintaining your devices battery levels.



- 1. Power Cord Inlet
- 2. Internal Power Button
- 3. Mode Selection Switch

- 4. External Switch Cable
- 5. LED Indicators
- 6. Auxiliary Outlets (*Always ON*)

- 7. Group Outlets "A"
- 8. Group Outlets "B"

HOW IT WORKS

Group Outlets "A"	Group Outlets "B"
7 Amp load ON ↓	5.5 Amp load OFF
5 Amp load OFF	5.5 Amp load ON ↓
5 Amp load ON ↓	4.5 Amp load OFF
4.5 Amp load ON	4.5 Amp load ON

QUICK START GUIDE

1. Plug in device adapters so there are an equal number of devices in Group A and Group B.
2. Make sure the Mode Selection Switch is set to "SMART" mode.
3. Plug in cart.

The Intelli-Sense timer will automatically sense the charging needs of the cart and start charging in the most efficient and quickest method.

With the Mode Selection Switch set to **SMART**:

Group Outlets "A" and Group Outlets "B" power on for 8 seconds in sequence then enter the following modes depending on current draw.

If the total current draw is greater than 9A:

The group outlets with the highest current draw will power on, while the group with less current draw remains OFF. Once the current draw difference is within 0.5A, the system will switch to the other group. When the total current is less than 9A, all outlets will power on at the same time.

If the total current draw is less than 9A:

Group "A" and Group "B" power on at the same time.

The total output is continuously monitored in case a new device is added.